



Shanghai King Chemical Co.,Ltd

Tel: +86-21-67817854 Fax: +86-21-67817855

Address: ROOM CDEF , 9th Floor, Building D, Weijing Center Tower
NO.2337 GuDal Road, Minhang District, Shanghai, China

Technical DataSheet

Titanium Dioxide Anatase Type Fiber Grade KCA-330

Application recommendation: chemical fiber.

Specifications

Item			KCA-330
TiO ₂ content	%	≥	98
105°C Volatile substance	%	≤	0.5
Water soluble matter	%	≤	0.6
Residue (45μm)	%	≤	0.1
Color (compared with standard sample)			商定 negotiation
Tint strength (compared with standard sample)		≥	100
PH (water suspension)			6.0-8.0
Oil absorption	g/100g	≤	—
Fe ₂ O ₃ content	%	≤	0.008
Water dispersibility	%	≥	75

*1、 Sample for Color、 tint strength and relative scattering efficiency is selected by Jinmao or agreed by customer. 2、 Sample for tint strength is selected by Jinmao 3、 Specifications which need negotiating are not within the scope of routine test, except that customer requires.

Package

Plastic woven bag, paper and plastic woven bag: 25kgs/bag, 500kgs/bag, 1000kgs/bag.

产品其它说明 Remark

Detailed technical data of the products, please contact the supplier; production quality index will be subject to supplier's test report.